


AUSTRALIAN STANDARD WIRE ROPE GRIP



Conforms to AS2076 and marked with AS and size under saddle.

- Heavy duty cast steel saddle and hi tensile U-bolt comes with larger nut size for greater tightening force.
- Sizes available are from 6mm to 52mm.
- Hot dipped galvanized finish on both U-bolt and saddle.
- NOT FOR LIFTING PURPOSES



CODE	SIZE (mm)	WEIGHT (kg/pc)	DIMENSIONS						
			A	B	C	D In	E	F	G
502406	6	0.04	14	15	20	M6	12	28	26
502408	8	0.069	18	19	22	M8	14	34	32
502410	10	0.12	20	23	27	M10	17	42	40
502412	12	0.132	22.3	28	32	M10	20	50	48
502414	14	0.223	27	32	38	M12	22	52	52
502416	16	0.351	31	32	41	M14	26	66	64
502418	18	0.488	35	38	47	M16	27	68	68
502420	20	0.98	43	46	58	M20	36	89	88
502422	22	1.123	40	46	61	M20	32	72	92
502426	26	1.425	50	50	66	M22	38	90	96
502428	28	1.56	52	50	70	M22	39	92	104
502432	32	1.9	56	55	75	M24	41	112	120
502438	38	2.1	64	55	78	M24	48	120	122
502444	44	3	73	62	90	M27	52	135	150



RANGER

LIFTING | RIGGING | SAFETY

RANGER.COM.AU | 1300 SLINGS

CODE	SIZE (mm)	WEIGHT (kg/pc)	DIMENSIONS						
502452	52	4.2	85	69	103	M30	56	154	185