



## G100 - ALLOY CHAIN

Ranger G100 Chain is European manufactured, generally used for Chain Slings with 25% higher lifting capacity than G80.

Manufactured

from hardened and tempered alloy steels and has a high resistance to

impact and wear to meet critical requirements of AS 2321 "Short Link

Chain for Lifting Purposes".


Chains are manufactured in Europe on German Wafios machines to

ensure high quality.

GRADE 100 LIFTING CHAIN

Ranger Product Catalogue

- Sizes available from 6mm to 32mm.
- Marked with chain grade and traceability mark.
- Made from G100 alloy steel with safety factor of 4 to 1.
- Conforms to AS 2321
- Batch tested, Test Certificates available upon request



CODE	SIZE (mm)	WLL (tonne)	WEIGHT (kg per m)	DIMENSIONS (mm)		
				B	C	D
149006	6	1.4	0.96	21	18	6
149008	8	2.5	1.4	28	24	8
149010	10	4	2.2	35	30	10
149013	13	6.7	3.8	46	39	13
149016	16	10	5.7	56	48	16
149020	20	16	9	70	60	20
149022	22	19	10.9	78	66	22

CODE	SIZE (mm)	WLL (tonne)	WEIGHT (kg per m)	DIMENSIONS (mm)		
149026	26	26.5	16.18	87	78	26
149032	32	40	24.1	107	96	32