



ROTATION RESISTANT 4 X 39

The 4 x 39 rotation resistant wire rope is supplied in drawn galvanized finish and fully lubricated for long service life. It is often used on Japanese crane brands and provides good rotation resistance.

- Robust construction for many hours of usage on board.
- Tensile strength is minimum 1960 N/mm².
- Fully lubricated in manufacturing

CODE	WIRE ROPE DIA		APPROX MASS (kg/100m)	MIN BREAKING FORCE 1960 N/mm ² (kN)
	mm	inches		
8C43910G	10		44.8	69.4
8C43912G	12		65.4	99.9
8C43914G	14		88.8	136.5
8C43916G	16		117.0	177.4
8C39418G	18		149.0	224.5
8C43919G	19		167.0	250.5
8C43920G	20		183.0	277.5
8C43922G	22		214.0	336.0
8C43922.3G		7/8	218.0	343.0
8C43924G	24		253.0	400.0
8C43925G	25		275.0	432.0
8C43925.4G		1	284.0	448.0
8C43926G	26		298.0	469.0
8C43928G	28		346.0	544.0
8C43930G	30		398.0	624.0
8C43932G	32		456.0	689.0
8C43934G	34		512.0	802.0
8C43936G	36		574.0	898.0
8C43938G	38		640.0	1002.0
8C43940G	40		709.0	1082.0
8C43942G	42		782.0	1192.0
8C43944G	44		859.0	1312.0
8C43945G	45		898.0	1372.0



RANGER

LIFTING | RIGGING | SAFETY

RANGER.COM.AU | 1300 SLINGS