

LEVER BLOCK ECONOMY

- Corrosive resistant zinc plated grade 100 load chain, high safety factor and long service life.
- Unique hand wheel & knob design-No preload required.
- Fused Brake Design-Proven durability that increases safety.
- Weston Style Dual Pawl Brake System- Double pawl design increases safety.
- Alloy Steel Hook- Industrial rated hooks rotate 360 degrees for easy rigging.
- Cast Steel Safety Latches- Increased durability with heavy duty safety latches secured with Allen screws and locknuts.
- Optional overload protection
- Specifications may vary slightly depending on manufacturer



CODE	Rated Capacity (tonne)	Standard Lift (m)	Running Load Test (kN)	Effort required to lift max. load (N)	No. of load chains	Load Chain	Minimum distance between hooks	Length of handle	DIMENSIONS			
									A	B	C	D
305075	0.8	1.5	1.2	145	1	5.6 x 15.7	280	245	146	96	119	26.5
305100	1	1.5	1.5	180	1	5.6 x 15.7	300	245	146	96	119	31.5
305200	1.6	1.5	2.4	200	1	7.1 x 19.9	335	265	164	100	126	35.5
305250	2.5	1.5	3.75	240	1	8.8 x 24.6	375	265	179	103	150	41
305300	3.2	1.5	4.8	280	1	10 x 28	395	415	196	114	159	43
305600	6.3	1.5	9.45	310	2	10 x 28	540	415	196	114	218	53
305900	9	1.5	13.5	350	3	10 x 28	680	415	196	114	298	64

