

RBG/VRBG LOAD RING

The RBG/VRBG Lifting points is ready for bolting with patented relief naps (up to RBG 15 t) protecting the fixing screws against bending and shearing loads. All versions with 100% crack detected bolts.



RBG-3 & VRBG-10T/16T

The patented relief lugs protect the securing bolt against bending and shearing loads. This provides additional safety. Stowable with smaller bolts and thus low profile. A forged ring according to AS4991, quality grade 80, electromagnetic crack detected and coloured red.

CODE	TYPE (tonne)	Thread Size	Single Leg	2, 3 or 4 Legs (maximum included angle)		
				60°	90°	120°
2909803	RGB 3 t	2 x M 16"	3	5.2	4.2	3
2909810	VRGB 10 t	4 x M 20"	10	17.3	14.1	10
2909816	VRGB 16 t	4 x M 30"	16	27.7	22.6	16
2909830	VRGB 31.5 t	6 x M 30"	30	52.0	42.4	30
2909850	VRGB 50 t	8 x M 26"	50	86.6	70.7	50
2909880	WBPG 80 t	6 x M 48"	80	138.6	113.1	80
2909910	WBPG 100 t	6 x M 48"	100			
2909920	WBPG 120 t	10 x M 48"	120			